


SPECIFICATION.

- MAXIMUM OPERATING PRESSURE.....10barg (145psig)
- MINIMUM OPERATING PRESSURE.....4barg (58psig)
- MAXIMUM FLOW RATE.....1.2m³/min (42scfm)
- RECOMMENDED OPERATING TEMPERATURE.....MAX. 30°C (86°F)
MIN. 1.5°C (35°F)

NOTE :-

ALL BAS-3015M PRODUCTS ARE SUPPLIED COMPLETE WITH AN 015ACS-4 12 MONTHS SUPPORT PACK, CONSISTING OF 4 x 015ACS CARTRIDGES.



ITEM	DESCRIPTION	REMARKS
8	BREATHING AIR CASE	BA1400
7	OUTLET MANIFOLD	1/4" MULTI PORT (F)
6	CO MONITOR	NTRON BACO 200
5	PRESSURE REGULATOR & GAUGE	-
4	'ACS' GRADE FILTER	AC5015CBMX
3	'AA' GRADE FILTER	AA015CBFX
2	'AO' GRADE FILTER	AO015CBFX
1	SAFETY COUPLER AND HOSETAIL	-

DETAIL OF INLET CONNECTION

Perberg
 Airtec
 Parker Hannifin Ltd
 Chesham, Bucks Valley
 Bucks HP8 4JF
 TEL +44 (0)1494 400 900
 FAX +44 (0)1494 402 600

REV DCU No. DATE NAME

C	004658	15/No.2013	LD
B	003231	12/Jan2013	LD
A	003792	14/Sep2012	LD
-	000964	27/Apr2011	DN

THIS DOCUMENT IS CONFIDENTIAL AND IS THE PROPERTY OF PARKER HANNIFIN LTD. IT IS TO BE KEPT IN STRICTLY CONFIDENTIAL AND NOT TO BE REPRODUCED OR TRANSMITTED IN ANY FORM OR BY ANY MEANS WITHOUT THE WRITTEN CONSENT OF THE COMPANY.

DRG. No 101-10116 SHEET 1 of 1