

## technical datasheet

### SEPREMIUM 30i

#### product features:

Catering to heavy-duty usage scenarios, the SEPREMIUM 30i supports compressed air flows up to 30 m<sup>3</sup>/min. This makes it an excellent choice for large-scale manufacturing plants or any facility that demands high throughput without compromising on filtration efficiency. Like the other models in the range, it features cutting-edge adsorption technology, final-stage activated carbon polishing, and a residual oil content of less than 5 ppm. Its lightweight, ergonomic filter elements simplify maintenance, while the built-in overflow light and optional remote sensor help avert downtime. If your site handles continuous, high-capacity workflows, the SEPREMIUM 30i delivers long-lasting performance, intelligent monitoring, and straightforward service.



#### commercial benefits:

- Ideal choice for compressor capacities up to 30 m<sup>3</sup>/min.
- Implementation of NEW high-quality JORC green filtration element
- Effective separation of mineral oil, synthetic oil and stable condensate emulsions
- Includes an Indicator Flashing Light; Optional JORC sensor to connect to your monitoring system also available
- Service valves, offering you draining of the individual towers for routine servicing and cleaning
- Brass hose connectors ensure swift and secure installation
- Exceptional value for money

**technical advantages:**

- Maximum compressor capacity 30 m<sup>3</sup>/min. (1250 CFM)
- Visual element life indication
- Lighter and easier replacement of elements
- Sectional draining options during servicing
- Multiple condensate inlets
- Overflow indicator
- Test valve & sample bottle for output testing/measuring the ppm value (indication)
- Operates with all JORC type drains (both timer controlled and zero air loss)
- Small foot print

**technical details:**

max. compressor capacity	30 m <sup>3</sup> /min.
max. oil adsorption	25 liters
Filter element	2
carbon element	1
inlet connection (2x)	G1/2", 10 mm hose adapter
outlet connection	G1", 26 mm hose adapter
test valve & sample bottle	yes
residual oil content	<5 ppm
overflow indicator	yes
housing material	PE
total recyclable	yes
housing colour	black
lid colour	grey
mount included	no
inlet and outlet hose pipe connectors	included
DIBt	Yes
dimensions	D400xW990xH900mm

**for separation of:**

mineral lubricants	yes
synthetic lubricants	yes
stable emulsions	yes (please consult pure!)
polyglycol	yes (please consult pure!)

**models, service kits, and accessories:**
**oil-water-seperator**

<b>order no.::</b>	<b>description:</b>
9830 PU	SEPREMIUM 30i
9830 PK	SEPREMIUM 30i KA
9830 PL	SEPREMIUM 30i PG

**oil-water-seperator comfort kit**
**incl. oil-water-seperator, service kit and drip tray**

<b>order no.:</b>	<b>description:</b>
98301 PU	SEPREMIUM 30i comfort kit
98301 PK	SEPREMIUM 30i KA comfort kit
98301 PL	SEPREMIUM 30i PG comfort kit

**service kits**

<b>order no.:</b>	<b>description:</b>
98309 PU	SEPREMIUM 30i service pack
98309 PK	SEPREMIUM 30i KA service pack
98305 PL	SEPREMIUM 30i PG service pack

**accessories**

<b>order no.:</b>	<b>description:</b>
963060	inner depressurizing foam for SEPREMIUM 30i
9045	multi-inlet adapter 3xG1/2"
950025	condensate self-test-kit
950020	sample bottle

All statements without guarantee