



Lloyd's
Register

Type Approval Certificate

This is to certify that the undernoted product(s) has/have been tested with satisfactory results in accordance with the relevant requirements of the Lloyd's Register Type Approval System.

This certificate is issued to:

PRODUCER	Parker Hannifin Manufacturing Limited
PLACE OF PRODUCTION	Dukesway Team Valley Trading Estate, Gateshead Tyne & Wear NE11 0PZ United Kingdom
DESCRIPTION	OIL-X Die-cast Filter Range
FILTRATION GRADE	AO General Purpose Coalescing and Dry Particulate Filters
TYPE	Die-cast: P010, P015, P020, P025, P030, P035, P040, P045, P050, P055 & P060
APPLICATION	Filters for compressed air, nitrogen and all relevant Group 2 gases
STANDARD	ISO12500-1:2007 Filters for Compressed Air – Test Methods – Oil Aerosols ISO8573-1:2010 Contaminant and Purity Classes ISO8573-2:2007 Test Methods for Oil Aerosol Content ISO8573-4:2001 Test Methods for Solid Particulate Content
RATINGS	Class 3 for oil as defined by ISO8573-1:2010 Class 2 for solid particulate as defined by ISO8573-1:2010

"This Certificate is not valid for equipment, the design, ratings or operating parameters of which have been varied from the specimen tested. The manufacturer should notify Lloyd's Register EMEA of any modification or changes to the equipment in order to obtain a valid certificate."

Certificate No.	16/ 00081(E1)
Issue Date	7 th October 2016
Expiry Date	6 th October 2021
Sheet	1 of 2

D. Hardacre
Lead Specialist – Design Appraisal
LR Inspection Services

Lloyd's Register EMEA
71 Fenchurch Street, London EC3M 4BS

Lloyd's Register EMEA
Is a subsidiary of Lloyd's Register Group

Lloyd's Register Group Limited, its affiliates and subsidiaries and their respective officers, employees or agents are, individually and collectively, referred to in this clause as the 'Lloyd's Register'. Lloyd's Register assumes no responsibility and shall not be liable to any person for any loss, damage or expense caused by reliance on the information or advice in this document or howsoever provided, unless that person has signed a contract with the relevant Lloyd's Register entity for the provision of this information or advice and in that case any responsibility or liability is exclusively on the terms and conditions set out in that contract.



The coalescing filter models described above and in Table 1 have been tested at ISO reference conditions, in accordance with the requirements of ISO12500-1:2007. Die-cast filter models were challenged with 40mg/ m³ of oil aerosol.

The measured residual oil content downstream of the test filters averaged <0.5mg/ m³, resulting in a downstream air purity equal to Class 3 for oil as defined by ISO8573-1:2010.

The initial dry differential pressure measured across each AO filter tested did not exceed 70mbar (1psi) and the initial saturated differential pressure measured across each AO filter tested did not exceed 125mbar (1.8psi).

The coalescing and dry particulate filter models described above have been tested in accordance with the requirements of ISO8573-4:2001.

The filter removed particles down to 1 micron resulting in downstream air purity equal to Class 2 for solid particulate as defined by ISO8573-1:2010.

Details of the equipment, methodology and results are contained within the Technical Documentation File COV1527423/ TDF.

The Design Appraisal Document No. COV1613518 O-32811/DH and its supplementary Type Approval Terms and Conditions form part of this Certificate

Table 1 : OIL-X Die-Cast Filter Range

AO - General Purpose Coalescing and Dry Particulate Filters

Test No.	LR Cert Reference	Issue	Standard	Yr Date	Inlet Oil Aerosol Challenge	Remaining Oil Content	Saturated Pressure Drop mbar (PSI)	Filter Grade	Models	Diecast - DC
1	COV0413801/1	6	ISO8573-2	2007	40 mg/m ³	<0.5 mg/m ³	<125 mbar (1.8 psi)	AO	(1)	DC
2	COV1527423/1	1	ISO12500-1	2007	40 mg/m ³	<0.5 mg/m ³	<125 mbar (1.8 psi)	AO	(2)	DC
Test No.	LR Cert Reference	Issue	Standard	Yr Date	Nominal Rating	Initial Dry Pressure Drop (*) mbar (PSI)	Filter Grade	Models	Diecast - DC	
3	COV0413801/4	3	ISO8573-4	2001	1 Micron	<70 mbar (1 psi)	AO	(3)	DC	
Models	(1) P010,P015,P020,P025,P030,P035,P040,P045,P050,P055 (2) P010,P015,P020,P025,P030,P035,P040,P045,P050,P055 & P060 (3) P010,P015,P020,P025,P030,P035,P040,P045,P050,P055									
Standards	ISO8573-2 Test Methods for Oil Aerosol Content ISO8573-4 Test Methods for Solid Particle Content ISO12500-1 Filters for Compressed Air - Test Methods - Part 1 Oil Aerosols (*) Defined as the maximum differential pressure for a new dry particulate filter									

Certificate No. 16/ 00081(E1)

Issue Date 7th October 2016

Expiry Date 6th October 2021

Sheet 2 of 2

D. Hardacre
Lead Specialist – Design Appraisal
LR Inspection Services

Lloyd's Register EMEA
71 Fenchurch Street, London EC3M 4BS

Lloyd's Register EMEA
Is a subsidiary of Lloyd's Register Group